Appl. No 10/587,850 Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008

- Claims

 1. (currently amended) Utility for reciprocal polarization with mutually complementary polarizing layers (cross-polarizer), distiguished by Complex polarizer system for reciprocal polarization (cross-polarizer), comprising an arrangement of
 - the position of each of said layers possessing Pi a described by its unit normal vector Ni, and its position vector Li: normal to Pi and a layer vector Vi coplanar to Pi, said Vi together with the optical axes if incidence and reflexion of Pi defining which directions of polarization of the electromagnetic radiation incident on Pi will be reflected (polarizing reflexion) resp. will transmit Pi (polarizing transmission) such that Vi together with the axis of reflexion of Pi span the plane of polarization of the reflected beam and Vi together with the axis of incidence of Pi span a plane, which is perpendicular to the plane of polarization of the transmitting beam, the polarization beam splitting characteristics of Pi described by a polarizing layer vector Vi coplanar to Pi such that light incident on Pi in Li along an incidence vector Ti is split into a transmitted beam with the plane of

polarization POPtrans: ((Vi × Ti) × Ti) o (X - Li) = 0 and a reflected beam

(the according reflection vector Ri being described by Ri=Ti - 2(Ti \circ Ni)Ni) with the POPref: (Vi × Ri) \circ (\times - Li) = 0, with (a \circ b) being the scalar

product of the two vectors a and b and with (a × b) being the cross product of the two vectors a and b:

- P1 and a given axis vector A1 defining axis vector A2= A1 $2(A1 \circ N1)N1$, and the planes E1: $(V1 \times A1) \circ (X L1) = 0$ and E3: $(V1 \times A2) \circ (X L1) = 0$;
- 1.2 polarizing layers P1 and P2 being arranged relative to said P1 and said along a first optical axis A1 such that V1 of P1 together with A1 span a plane E1 that is perpendicular to the plane E2 spanned by V2 of P2 and A1 (designated by the term "mutual complementarity" of P1 and P2), L2 = L1 + d2* A1;

(V2 × A1) • (V1 × A1) =0; (plane E2: (V2 × A1) • (X - L2) = 0 being

perpendicular to plane E1):

1.3 polarizing layers P1 and P3 being arranged relative to said P1 and said

- Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008 Appl. No 10/587,850
 - along a second optical axis A2 such that V1 of P1 together with A2 span a plane E3 that is perpendicular to the plane E4 spanned by V3 of P3 and A2 (designated by the term "mutual complementarity" of P1 and P3), L3 = L1 + d3* A2;

- $(V3 \times A2) \circ (V1 \times A2) = 0$; (plane E4: $(V3 \times A2) \circ (X L3) = 0$ being perpendicular to plane E3).
- 1:4 optical axes A1 and A2 intersecting in P1, cutting angle between N1 and S1 equalling cutting angle between N1 and 52,
- 1.5the polarizing layers being positioned such that reciprocal polarization is achieved, characterized by a transmission at P1 being coupled to a reflexion at P2 along the axis A1 and a reflexion at P1 being coupled to a transmission at P3 along the axis A2 are coupled (designated by the term "reciprocal polarization").
- Cross-polarizing system Complex polarizer system for 2. (currently amended) reciprocal polarization (cross-polarizer) according to claim 1, said polarization layers Pi being cartesian polarizers, characterized by having their polarization planes selectable independently from the plane of incidence, and said polarization layers Pi being arranged in planes which are perpendicular to a common ground plane, and all said optical axes being coplanar to a common ground plane.
- 3. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 2, said polarizing layer vector V1 of P1 and said polarizing layer vector V2 of P2 being perpendicular to each other.
- 4. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 3, said polarizing layers P2 and P3 forming a common polarization layer.
- 5. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 1, comprising
- 5.1 comprising at least one right triangular prism (with all lateral surfaces perpendicular to its footprint) with a triangular footprint composed of two

- Appl. No 10/587,850 Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008 right prisms (with all lateral surfaces perpendicular to the footprint) T1 and T2 each with an isosceles triangular footprint, base;
- 5.2 the lateral surface of sub-prism T2 in-between the two sub-prisms carrying a cartesian polarization layer P1[[,]];
- 5.3 the lateral surface of subprism T1, which together with a lateral surface of subprime-prism T2 forms a common lateral surface of the compound said composed prism, carrying a cartesian polarization layer P2.
- 6. (currently amended) <u>Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer)</u> according to claim 1, <u>comprising containing at least</u> a right prism (with all lateral surfaces perpendicular to its footprint) with an isosceles triangular footprint <u>base</u>;

 the two lateral surfaces of equal size <u>of said prism</u> carrying mutually complementary polarizations layers.
- 7. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 1, comprising an additional fourth polarization layer P4 which together with said P2 along a third optical axis A3 and together with said P3 along a fourth optical axis A4 constitutes an additional cross-polarizer according to claim 1.
- 8. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 7, polarization layers P1 and P4 having parallel polarizing layer vectors and being coplanar within a common plane E1, and the polarization layers P2 and P3 having parallel polarizing layer vectors and being coplanar within a common plane E2, and E1 and E2 all four layers having an intersection line where all four polarization layers meet.
- 9. (withdrawn amended) Utility for reciprocal polarization with mutually complementary polarizing layers (cross-polarizer), distinguished by

 Complex polarizer system for reciprocal polarization (cross-polarizer) comprising

 9.1 comprising at least two polarizing layers Pi (i=1,2...)[[,]]:
 said layers each possessing Pi characterized by a normal vector Ni normal to Pi and a polarizing layer vector Vi coplanar to Pi; [[,]]
 said Pi having beam splitting properties, which split an incident beam into a transmitting and a reflected beam:

01/10/2008 18:35

Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008 Appl. No 10/587,850

said Vi together with the optical axis if incidence and reflection of Pi defining which directions of polarization of the electromagnetic radiation incident on Pi will be reflected (polarizing reflexion) resp. will transmit Pi (polarizing transmission) such that Vi together with the axis of reflexion of Pi span the plane of polarization of and the reflected beam spanning the plane of polarization of the reflected beam;

- and said Vi together with the axis of incidence of Pi span a plane and the transmitting beam spanning a plane perpendicular to the plane of polarization of the transmitting beam;
- 9.2 polarizing layers
- P1 and P2 a further polarizer being arranged along a first optical path S1, which is folded by a reflecting means (n-1,2,3,...) such that the plane E1[[,]] which is spanned by V1 and the optical axis of \$1 in P1, and the plane E2[[,]] which is spanned by V2 the layer vector of said further polarizer and the optical axis of S1 in P2 said further polarizer; , have a correlation such that the mirrored plane E1*, which is derived from E1 by successive reflexions at said n reflecting means, is perpendicular to E2 (designated by the term "mutual complementarity" of P1 and P2),
- said two polarizing layers being mutual complementary, characterized by the plane E1*, derived from E1 by optional means for folding, being perpendicular to E2:
- 9.3 polarizing layers
- P1 and P2 a further polarizer being arranged along a second optical path S2, which may be folded by n reflecting means (n=0,1,2,...) such that the plane E3[[,]] which is spanned by V1 and the optical axis of S2 in P1, and a plane E4[[,]]which is spanned by V2 the layer vector of said further polarizer and the optical axis of \$2 in P2 said further polarizer; ; have a correlation such that the mirrored plane E3*, which is derived from E3 by successive reflexions at said n reflecting means, is perpendicular to E4 (designated by the term "mutual complementarity" of P1 and P2),
- said two polarizing layers being mutual complementary, characterized by the plane E3*, derived from E3 by optional means for folding, being perpendicular to E4:
- 9.4 said two optical paths \$1 and \$2 intersecting in P1 with equal intersecting angles between N1 and S1 and between N1 and S2[[,]];
- 9.5 the architecture of the system coupling the transmission at P1 along S1 to a reflection at the further polarizer along S1 and the corresponding reflection

Appl. No 10/587,850 Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008 at P1 to a transmission at P2 the further polarizer along \$2.

- 10. (withdrawn amended) Utility for reciprocal polarization with mutually complementary polarizing layers (cross-polarizer), distinguished by Complex polarizer system for reciprocal polarization (cross-polarizer) comprising 10.1 comprising at least three polarizing layers Pi (i=1,2,3,..)[[,]];

 each of said layers possessing Pi characterized by a normal vector Ni normal to Pi and a polarizing layer vector Vi coplanar to Pi; [[,]] said Pi having beam splitting properties, which split an incident beam into a
 - transmitting and a reflected beam:

 said Vi together with the optical axis if incidence and reflection of Pi defining which directions of polarization of the electromagnetic radiation incident on Pi will be reflected (polarizing reflexion) resp. will transmit Pi (polarizing transmission) such that Vi together with the axis of reflexion of Pi span the plane of polarization of and the reflected beam spanning the plane of
 - polarization of the reflected beam;

 and said Vi together with the axis of incidence of Pi span a plane and the transmitting beam spanning a plane perpendicular to the plane of polarization of the transmitting beam;
 - 10.2 polarizing layers
 - P1 and P2 being arranged along a first optical path \$1, which is folded by n reflecting means (n=1,2,3,...) such that the plane E1[[,]] is spanned by V1 and the optical axis of \$1 in P1, and the plane E2[[,]] which is spanned by V2 and the optical axis of \$1 in P2; have a correlation such that the mirrored plane E1*, which is derived from E1 by successive reflexions at said n reflecting means, is perpendicular to E2 (designated by the term "mutual complementarity" of P1 and P2),
 - said polarizing layers P1 and P2 being mutual complementary, characterized by the plane E1*, derived from E1 by optional means for folding, being perpendicular to E2;
 - 10.3 polarizing layers
 - P1 and P3 being arranged along a second optical path S2, which may be folded by n reflecting means (n=0,1,2,...) such that the plane E3[[,]] which is spanned by V1 and the optical axis of S2 in P1, and a plane E4[[,]] which is spanned by V3 and the optical axis of S2 in P3; have a correlation such that the mirrored plane E3*, which is derived from E3 by successive reflexions at said n reflecting means, is perpendicular to E4 (designated by the term

- Appl. No 10/587,850 Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008

 "mutual complementarity" of P1 and P2},
 - said polarizing layers P1 and P3 being mutual complementary, characterized by the plane E3*, derived from E3 by optional means for folding being perpendicular to E4;
 - 10.4 said two optical paths \$1 and \$2 intersecting in P1 with equal intersecting angles between N1 and \$1 and between N1 and \$2[[,]];
 - 10:5 the architecture of the system coupling the transmission at P1 along S1 to a reflection at P2 and the corresponding reflection at P1 to a transmission at P3 along S2.
- 11. (withdrawn amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 10, comprising an additional fourth polarizing layer P4, which together with said P2 along a third optical path S3 and together with said P3 along a fourth optical path S4 constitutes an additional cross-polarizer according to claim 10.
- 12. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 10-1, at least one of said layers Pi being a doubled or two-sided cartesian polarizer with parallel layer vectors Vi.
- 13. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 10 1, all of said Pi being cartesian polarizers, e.g. wire grid polarizers.
- 14. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 10-1, all of said Pi being thin-film polarizers working according to Browster's law of the MacNeille type.
- 15. (currently amended) Cross-polarizing system Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 10-1, all of said Pi being contained in a body and the optical paths into and out of the cross-polarizing system being made possible by windows or openings.
- 16. (currently amended) Utility for the light architecture in a two-channel display system, distinguished by Complex polarizer system for reciprocal polarization

- Appl. No 10/587,850 Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008
 - (cross-polarizer) according to claim 1, further comprising

+49-9453996618

- 16.1 comprising at least one cross-polarizing system according to claim 10,
- 16.2 comprising at least one two spatial light modulators in each channel, ;
- 16.3 one of said cross said polarizinger system[[s]] being used to feed the spatial light modulators with polarized light.
- 17. (currently amended) Utility for the light architecture in a two-channel display system, distinguished by Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 1, further comprising
- 17.1- comprising at least one cross-polarizing system according to claim 10,
- 17.2 comprising at least one two spatial light modulators in each channel, ;
- 17.3 one of said cross said polarizinger system[[s]] being used to superpose the modulated light from the spatial light modulators.
- 18. (currently amended) Utility for the light architecture in a two-channel display system, distinguished by Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 1, further comprising
- 18.1 comprising a cross-polarizing system according to claim 10,
- 18.2 comprising at least one two spatial light modulator of the type micro-electro-mechanical-system (MEMS, e.g. DMD by Texas Instruments) in each channel, :
- 18.3 said cross-polarizinger system being used to both feed the spatial light modulators with polarized light and to superpose the modulated light from the spatial light modulators[[,]]
- 18.4 the plane of incidence in said P1 intersecting the plane of superposition with an angle different from 0 degree.
- 19. (withdrawn amended) Utility for the light architecture in a two-channel display system, distinguished by Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 9, further comprising
- 19.1 comprising a cross-polarizing system according to claim 9,
- 19.2 comprising at least one spatial light modulator in each channel positioned in said optical paths \$1 and \$2 between P1 and P2.
- 20. (currently amended) Utility for the light architecture in a two-channel display system, distinguished by Complex polarizer system for reciprocal polarization (cross-polarizer) according to claim 15, further comprising
- 20.1 comprising a cross-polarizing system according to claim 15;

Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008 Appl. No 10/587,850

- 20.1 comprising at least one spatial light modulator in each channel which is mounted to the body.
- 21. (currently amended) Complex polarizer system for reciprocal polarization (crosspolarizer) Cross-polarizing system according to claim 1, comprising at least one right triangular prism (where the lateral surfaces are perpendicular to the footprint) with the footprint of a triangle; said prism being which is composed of two right triangular sub-prisms with the base of an isosceles triangle each, such that with a thin-film type polarizing layer P1 with its layer vector V1 being is situated between these two subprisms[[,]]; and
 - the lateral surface of the compound prism that which consists of two lateral surfaces of the sub-prisms[[,]] carries carrying a cartesian polarizing layer P2 with the its layer vector V2;
 - V2 beina perpendicular to V1.
- 22. (currently amended) Complex polarizer system for reciprocal polarization (crosspolarizer) Cross-polarizing system according to claim 1, comprising at least one right triangular prism (where the lateral surfaces are perpendicular to the footprint) with the footprint of a triangle, : said prism being which is composed of two right triangular sub-prisms with the footprint base of an isosceles triangle each, such that with a cartesian type polarizing layer P1 with its layer vector V1 being is situated between these two sub-prisms[[,]]; and
 - the lateral surface of the compound prism that which consists of two lateral surfaces of the sub-prisms[[,]] carries carrying a cartesian polarizing layer P2 with the its layer vector V2 perpendicular to V1.
- 23. (currently amended) Complex polarizer system for reciprocal polarization (crosspolarizer) Cross-polarizing system according to claim 1, comprising at least one right triangular prism (where the lateral surfaces are perpendicular to the footprint) with the footprint of a triangle, :
 - said prism being which is composed of two right triangular sub-prisms T1a, T1b with the footprint base of an isosceles triangle each[[,]];
 - such that those lateral surfaces of the compound prism, which that consist[[s]] of only one lateral surface of the sub-prisms, carries carrying polarization layers

+49-9453996618

- Appl. No 10/587,850 Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008
- 24. (currently amended) Complex polarizer system for reciprocal polarization (cross-polarizer) Cross-polarizing system according to claim 1, comprising at least one right triangular prism (where the lateral surfaces are perpendicular to the footprint) with the footprint of a triangle, ;

aid prism being which is composed of two right sub-prisms with the footprint base of an isosceles triangle each[[,]];

- such that a thin-film type polarizing layer P1 is being situated between these two sub-prisms.
- 25. (currently amended) Complex polarizer system for reciprocal polarization (cross-polarizer) Cross-polarizing system according to claim 10 1.
 all cartesian polarizing layers being doubled or two-sided.
- 26. (new) Method of using a cross-polarizer according to claim 1.
- 27. (new) Method for reciprocal polarization (cross-polarization), using a light source;
 - using three polarization beam splitting layers Ptrans1ref1, with a polarizing layer vector Vtrans1ref1, Pref2, with a polarizing layer vector Vtrans2, with a polarizing layer vector Vtrans2;
 - using the optical axis Atrans1 and the optical axis Aref1 which is derived from Atrans1 by mirroring Atrans1 at the plane of Ptrans1ref1;
 - using a polarized beam Btrans1ref2, which transmits Ptrans1ref1 along Atrans1, located between Ptrans1ref1
 - using a polarized beam Bref1trans2, which is reflected at Ptrans1ref1 along Aref1; arranging Btrans1ref2 and Bref1trans2 such that they form a common beam with both polarization components of Btrans1ref2 and Bref1trans2 on one side of Ptrans1ref1;
 - choosing Vtrans1ref1 such that the plane of polarization of Btrans1ref2 is perpendicular to the plane spanned by Vtrans1ref1 and Atrans1, and that the plane of polarization of Bref1trans2 is spanned by Aref1 and Vtrans1ref1;
 - guiding Btrans1 ref2 on an optical path between Ptrans1 ref1 and Pref2;
 - arranging Prof2 such that the optical path of Btrans1ref2 leads to Prof2 in the optical axis Aref2;
 - arranging Pref2 such that Birans1ref2 is reflected at Pref2 by choosing Vref2 such that

01/10/2008 18:35

Amdt. dated Sept,28,2008 Reply to Office Action of Sept,2, 2008 Appl. No 10/587,850

> the plane of polarization of Btrans1ref2 is spanned by Aref2 and Vref2, therefore coupling the transmission of Btrans1ref2 at Ptrans1ref1 to a reflection of Btrans1 ref2 at Pref2;

guiding Bref1trans2 on an optical path between Ptrans1ref1 and Ptrans2;

- arranging Ptrans2 such that the optical path of Bref1trans2 leads to Ptrans2 in the optical axis Atrans2;
- arranging Ptrans2 such that Bref1trans2 transmits at Ptrans2 by choosing Vtrans2 such that the plane of polarization of Brefitrans2 is perpendicular to the plane spanned by Atrans2 and Vtrans2, therefore coupling the reflection of Bref1 trans at Ptrans1ref1 to a transmission of Bref1trans2 at Ptrans2.
- 28. (new) Method for reciprocal polarization (cross-polarization), using a light source;
 - using four polarization beam splitting subprocesses (either a polarizing transmission or a polarizing reflection of a common polarization split process) Ptrans1, Prof1, Prof2, Ptrans2;
 - using a polarized beam Brans1 ref2, transmitting at the process Ptrans1; using a polarized beam Bref1trans2, which is reflected at Pref1;
 - said Ptrans1 and Pref1 subprocesses being the polarizing transmission subprocess and polarizing reflection subprocess of a common polarization split process;
 - sending Btrans1 ref2 through the polarizing reflection subprocess Pref2, thus coupling the polarizing transmission Ptrans1 of Btrans1 ref2 to the polarizing reflection Pref2 of Birans 1 ref2;
 - sending Bref1trans2 through the polarizing transmission subprocess Ptrans2, thus coupling the polarizing reflection Pref1 of Bref1trans2 to the polarizing transmission Ptrans2 of Bref1trans2.